

Elcometer 112AL Punched Wet Film Combs (Aluminium)

These punched aluminium combs offer the user a low cost method of measuring the wet film thickness.

The Elcometer 112AL, being punched from aluminium, is not as accurate as precision formed stainless steel wet film combs and has a shorter lifespan.

Supplied in a pack of 10 combs, each comb has Metric (25 - 3000 μ m) on one side and Imperial (1 - 118mils) on the other.

The Elcometer 112AL can be customised with your logo.

Please contact Elcometer for further details.



STANDARDS:

ASTM D 4414-A, AS/NZS 1580.107.3, BS 3900-C5-7B,
 ISO 2808-1A, ISO 2808-7B, JIS K 5600-1-7, NF T30-125, US
 Navy PPI 63101-000, US Navy NSI 009-32

Elcometer 112 & 3236 Hexagonal Wet Film Combs (Stainless Steel)

These hexagonal precision formed stainless steel wet film combs are long lasting, reusable and supplied in a range of thicknesses measuring up to 3000 μ m (120mils).

These six sided combs vary in size, giving either 24 or 36 measurement steps, depending upon the comb, thus providing increased accuracy.



STANDARDS:

ASTM D 4414-A, AS/NZS 1580.107.3, BS 3900-C5-7B,
 ISO 2808-1A, ISO 2808-7B, JIS K 5600-1-7, NF T30-125, US
 Navy PPI 63101-000, US Navy NSI 009-32

Elcometer 112AL Punched Wet Film Combs (Aluminium)

Technical Specification

Part Number	Description
B112AL12473-3	Elcometer 112AL Aluminium Wet Film Comb (Pack of 10)
Dimensions	75 x 65 x 1mm (2.95 x 2.56 x 0.04")
Weight	90g (3.17oz)
Packing List	Elcometer 112AL (Pack of 10) and operating instructions

Elcometer 112 & 3236 Hexagonal Wet Film Combs (Stainless Steel)

Technical Specification

C

Part Number	Range	Values	Certificate
K0003236M201	20 - 370µm	20, 30, 40, 50, 60, 70, 80, 90, 100, 110, 120, 130, 150, 170, 190, 210, 230, 250, 270, 290, 310, 330, 350, 370µm	○
K0003236M202	25 - 2000µm	25, 50, 75, 100, 125, 150, 175, 200, 225, 250, 275, 300, 350, 400, 450, 500, 550, 600, 650, 700, 750, 800, 850, 900, 950, 1000, 1100, 1200, 1300, 1400, 1500, 1600, 1700, 1800, 1900, 2000µm	○
B112----1B	25 - 3000µm	25, 50, 75, 100, 125, 150, 175, 200, 225, 250, 275, 300, 350, 400, 450, 500, 550, 600, 650, 700, 750, 800, 850, 900, 1000, 1100, 1200, 1400, 1600, 1800, 2000, 2200, 2400, 2600, 2800, 3000µm	○
K0003236M203	0.5 - 15mils	0.5, 0.75, 1.0, 1.25, 1.5, 2, 2.5, 3, 3.5, 4, 4.5, 5, 5.5, 6, 6.5, 7, 8, 9, 10, 11, 12, 13, 14, 15mils	○
K0003236M204	1 - 80mils	1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 12, 14, 16, 18, 20, 22, 26, 28, 30, 32, 34, 36, 38, 40, 42, 44, 46, 48, 50, 55, 60, 65, 70, 75, 80mils	○
B112----2B	1 - 120mils	1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 14, 16, 18, 20, 22, 26, 28, 30, 32, 34, 36, 38, 40, 45, 50, 55, 60, 70, 80, 90, 100, 110, 120mils	○
Dimensions and Weight	Elcometer 3236 M201 / M203	53 x 50 x 1mm (2.09 x 1.97 x 0.04"), 10g (0.35oz)	
	Elcometer 3236 M202 / M204	77 x 90 x 1mm (2.95 x 3.54 x 0.04"), 22g (0.77oz)	
	Elcometer 112	75 x 65 x 1mm (2.95 x 2.54 x 0.04"), 20g (0.7oz)	
Packing List	Wet Film Comb, storage case and operating instructions		

○ Optional Calibration Certificate available.