

Elcometer Frikmar Viscosity Dip Cups



Elcometer Frikmar Viscosity Dip Cups

Thanks to its handle, this cup is very easy to use to perform checks on site or during the manufacturing process. It is ideal for measuring the consistency of paints, varnishes and similar products.

The cup is first dipped into the product to be measured, then the contents empty through the orifice. The measured kinematic viscosity is generally expressed in seconds (s) flow time, which can be converted to Centistokes (cSt) if the Standard stipulates a conversion method.

Several ranges are available, according to Standards; from 7 to 1100cSt.

Viscosity

The extent to which a liquid resists a tendency to flow is defined as viscosity. In the coatings industry, this behaviour is one of the key parameters.

Elcometer manufactures and supplies a wide range of viscosity gauges from flow cups and dip cups to rotational viscometers

Flow Cups: The process of flow through an orifice can often be used as a relative measurement and classification of viscosity. This measured kinematic viscosity is generally expressed in seconds of flow time which can be converted into Centistokes using a viscosity disc calculator.

Dip Cups: Using the same principle to the flow cups, dip cups – Frikmar, Zahn, Shell, etc – can be used to provide a quick viscosity measurement on the shop floor or on site

Rotational: Rotational viscometers are used to determine the viscosity of liquids which do not depend solely on temperature and pressure. The behaviour of non-Newtonian liquids can be determined using a range of rotational viscometers.

At a glance:

Handle for ease of use

Expressed in seconds (s) flow time but can be converted to Centistokes (cSt)

Part Number		Description	Cup No.	Orifice Diameter	Range (cSt) [†]
Without Certificate	With Certificate				
K0002434M001	K0002434M001C ^(d)	Elcometer 2434 DIN Dip Cup Can be used in accordance with: DIN 53211 (cup 4 only)	2	2mm	-
K0002434M002	K0002434M002C ^(e)		4	4mm	96 - 683
K0002434M003	K0002434M003C ^(d)		6	6mm	-
K0002434M004	K0002434M004C ^(d)		8	8mm	-
K0002435M001	K0002435M001C ^(e)	Elcometer 2435 ASTM/FORD Dip Cup Can be used in accordance with: ASTM D 1200	4	4.12mm	70 - 370
K0002436M001	-	Elcometer 2436 AFNOR Dip Cup Can be used in accordance with: AFNOR NF T30-014	4	4mm	50 - 1100
K0002437M002	K0002437M002C ^(e)	Elcometer 2437 ISO Dip Cup Can be used in accordance with: ASTM D 5125, DIN 53224, EN 535, ISO 2431, NBN T22-108, NF T30-070	3	3mm	7 - 42
K0002437M003	K0002437M003C ^(e)		4	4mm	34 - 135
K0002437M006	K0002437M006C ^(e)		5	5mm	91 - 326
K0002437M004	K0002437M004C ^(e)		6	6mm	188 - 684
K0002437M005	K0002437M005C ^(d)		8	8mm	-

[†] For information only
^(d) Dimensional Certificate
^(e) Efflux Time Certificate

Elcometer Viscosity Cup Standard Calibration Oils



Elcometer 2410 Calibration Oils

In order to check a viscosity cup's calibration or to certify it for ISO purposes, it is imperative that viscosity cup standard calibration oils are used.

Standard oils have a specified drain time, dependent upon the viscosity cup type (Ford, Shell, Zahn, etc) and the orifice size or cup number used.

To check the viscosity cup, use the standard viscosity oils in place of the liquid and measure the drain time.

Specific calibration oils can only be used with specific flow and dip cups. Please refer to the table below to establish which oil is required for each cup.

All viscosity oils are supplied in ½ litre (1 pint) bottles.

At a glance:

To check the viscosity cup's calibration and certify it for ISO purposes

The specific drain time is dependent on the cup type

Replace your liquid with the standard oils to measure drain time

Part Number	Range at 25°C (77°F)	Cup Type	Cup No.	Model	Orifice Diameter
K0002410M022	60 – 120cSt	DIN Frikmar Dip Cup	4	Elcometer 2434/2	4mm
K0002410M023	100 – 230cSt	DIN Frikmar Dip Cup	4	Elcometer 2434/2	4mm
K0002410M024	200 – 460cSt	DIN Frikmar Dip Cup	4	Elcometer 2434/2	4mm
K0002410M021	20 – 34cSt	ISO Frikmar Dip Cup	3	Elcometer 2437/2	3mm
K0002410M022	60 – 120cSt	ISO Frikmar Dip Cup	4	Elcometer 2437/3	4mm
K0002410M023	100 – 230cSt	ISO Frikmar Dip Cup	6	Elcometer 2437/4	6mm
K0002410M024	200 – 460cSt	ISO Frikmar Dip Cup	6	Elcometer 2437/4	6mm

Related Products



Elcometer 7300 Stopwatch

Elcometer 7300 High Precision Stopwatch:

Measuring intervals: 1/100 second for 30 minutes and 1 second for 24 hours. Time / calendar display, 12/24 hour mode.

Part Number: K0007300M201



Elcometer 2400 Conversion Disc

Elcometer 2400 Conversion Disc:

Allows viscosity (cSt) and flow times of different cups to be compared.

Part Number: KT002400N003



Elcometer Frikmar Cup Stand

Elcometer Frikmar Cup Stand:

A useful, compact way of storing dip cups when not in use. Can hold up to 5 cups.

Part Number: K0002999M002

ENGLAND

Elcometer Ltd
Edge Lane
Manchester M43 6BU

Tel: +44 (0)161 371 6000
Fax: +44 (0)161 371 6010
e-mail: sales@elcometer.com
www.elcometer.com

USA

Elcometer Inc
1893 Rochester Industrial Drive
Rochester Hills Michigan 48309

Tel: +1 248 650 0500
Toll Free: 800 521 0635
Fax: +1 248 650 0501
e-mail: inc@elcometer.com
www.elcometer.com

CANADA

Elcometer Ltd
PO Box 622, 401 Ouelette Avenue
Windsor, Ontario N9A 6N4

Tel: +1 248 650 0500
Toll Free: 800 521 0635
Fax: +1 248 650 0501
e-mail: ca_info@elcometer.com
www.elcometer.com

ASIA & THE FAR EAST

Elcometer (Asia) Pte Ltd
896 Dunearn Rd
Sime Darby Centre #3-09
Singapore 589472,
Republic of Singapore

Tel: +65 6462 2822
Fax: +65 6462 2860
e-mail: asia@elcometer.com
www.elcometer.com

BELGIUM

Elcometer SA
Rue Vallée 13
B-4681 Hermalle /s Argenteau

Tel: +32 (0)4 379 96 10
Fax: +32 (0)4 374 06 03
e-mail: be_info@elcometer.be
www.elcometer.be

FRANCE

Elcometer Sarl
97 Route de Chécý
45430 BOU

Tel: +33 (0)2 38 86 33 44
Fax: +33 (0)2 38 91 37 66
e-mail: fr_info@elcometer.fr
www.elcometer.fr

GERMANY

Elcometer Instruments GmbH
Ulmer Strasse 68
D-73431 Aalen

Tel: +49 (0)7361 52806 0
Fax: +49 (0)7361 52806 77
e-mail: de_info@elcometer.de
www.elcometer.de